



SF100-2PRV-L HYDRONIC SYSTEM FEEDER TECHNICAL INFORMATION

DIMENSIONS :

WEIGHT : 31 kg, 67.5 lbs (Empty)

PUMP ELECTRICAL :

115/60/1, 0.7 amps
3-prong plug and cord

PUMP PERFORMANCE :


0.09 l/s (1.4 gpm) @ free flow
0.06 l/s (1.0 gpm) @ 345 kPa (50 psig)
Self-priming up to 2.1 m (7 feet)
Maximum liquid temp. 77 C (170 F)



Certified to CAN/CSA
C22.2 No. 68

Intertek
9901055

Conforms to
UL 73



MIXING & STORAGE TANK

120 USG (454 LITRES)

SPECIFICATION :

Hydronic system feeder shall be AXIOM INDUSTRIES LTD. Model SF100-2PRV-L. System shall include 454 litre (120 US gallon) storage/mixing tank with cover; pump suction hose with inlet strainer; pressure pump with thermal cut-out; integral pressure switch; integral check valve; cord and plug; pre-charged accumulator tank with EPDM diaphragm; manual diverter valve for purging air and agitating contents of storage tank; two adjustable pressure regulating valves adjustable (35 – 380 KPa; 5 – 55 psig) each complete with pressure gauge; built-in check valve; union connection; 12 mm (½”) x 900 mm (36”) long flexible connection hose with check valve; low level pump cut-out. Pressure pump shall be capable of running dry without damage. Power supply 115/60/1 0.7 A. Unit shall be completely pre-assembled and certified by a recognized testing agency to CSA standard C22.2 No 68.

OPTIONAL ACCESSORIES :

☐ **RIA10-1-SAA** -- Low level Alarm Panel c/w Remote Monitoring Dry Contacts and Selectable Audible Alarm

LIMITED WARRANTY :

The SF100-2PRV-L is warranted against defects in materials and workmanship for one year.

Project

Location

Consultant

Contractor

Unit Tag

Sales Agent